

Pins acc.
DIN 72552

L ⊗ turn signal left
R ⊗ turn signal right
58 3-point connector tail light

15
15
30
30
fuse box, 2 fuses 10A
red
red/black
red/black

15
switched +
red

30
battery +
red/black

white
green
brown
2-point connector

orange/blue

red/black

red/black

orange/blue

orange/blue

control lamp hazard
hazard switch
battery +

relay hazard
B battery +
L hazard switch

to hazard switch

black
white
yellow
blue
green
grey/orange
violet
brown
red
9-point connector

multifunction switch
ground
turn signal left
high beam
driving light
turn signal right
turn signal switch
horn
parking light
switched +

black
green
yellow/red
red
white
yellow
6-point connector

speed indicator
ground
turn signal indicator right
flasher
switched +
turn signal indicator left
high beam control lamp

black/white
grey/orange
yellow/red
black

turn signal relay
L turn signal switch
B switched +
E ground -

ground

black
brown
yellow
green
4-point connector

front head light/ turn signal right
ground -
parking light
high beam
turn signal right

black
red
violet

horn
ground
switched +
horn switch

black
brown
blue
white
4-point connector

front head light/ turn signal left
ground
parking light
driving light
turn signal left

Pins acc.
DIN 72552

49a
30

49
49a

31

L
56a

56b
R
49a

58
15

31

R
49

15
L
56a

49a

49
31

31

31

58
56a
R

31

15

31

58
56b
L

wiring diagram harness schematic
(01/2006)